


SPECIFICATIONS

Modèle	GeForce RTX™ 4090 SUPRIM 24G
Processeur graphique	NVIDIA® GeForce RTX™ 4090
Cœurs	16384 unités
Mémoire	24 Go GDDR6X
Bus Mémoire	384-bit
Fréquence du GPU	Performances extrêmes : 2610 MHz (MSI Center) Boost : 2595MHz (Modes GAMING et SILENT)
Vitesse mémoire	21 Gb/s
Nombre de moniteurs supportés	4
Technologie G-SYNC™	Oui
Résolution numérique maximum	7680 x 4320
Support du procédé HDCP	Oui
Bloc d'alimentation recommandé	1000 watts (Min. 850 watts)
Connecteurs alimentation	1 x 16 broches
Sorties	3 x DisplayPort (v1.4a) 1 x HDMI™ (Support 4K @ 120 Hz HDR, 8K @ 60 Hz HDR et de la fréquence de rafraîchissement variable telle que spécifiée par la norme HDMI™ 2.1a)
Version OpenGL	4.6
Dimensions	336 x 142 x 78 mm
Poids	2413 g / 3636 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.




Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.